

PRODUCT INFORMATION

A+



- Flue gas outlet mounted from the inside of the combustion chamber, diameter 150 mm, allows for installation in existing open furnaces.
- An automatic fan assembly circulates warm air in the room (optional).
- The deepened furnace means safety and the possibility of larger loads of wood.
- A massive and durable combustion chamber made of Akuceram significantly affects the ecology of wood combustion.
- Air inlet fi 100 mm (mounted on the back or bottom) allows the installation of the cassette also at home with recuperation.
- Built-in possibility of connecting the cassette to the hot air distribution system (2 x fi 100 mm).
- The new air supply and circulation system is a comprehensive solution that guarantees ecological burning of wood and a beautiful, clear vision of fire.
- New door design with minimalist elegance of Decor glass.
- Intuitive combustion control with a single throttle.

Nominal power [kW]	8,0
Heating load range [kW]	4,0-10
Thermal efficiency [%]	85
CO emission (by 13% O ₂) [g/m ³]	0,891
CO emission (by 13% O ₂) [%]	0,0713
Dust emission [g/m ³]	0,023
Exhaust temperature [°C]	170
Average fuel consumption [kg/h]	2,4
Maksimum log lenght [mm]	350
Dimensions of the glass in fireplace [mm]	640x481
External dimensions [mm]	700x540x470
Flue diameter [mm]	150
Air intake diameter [mm]	100
Weight [kg]	114
Efficiency coefficient	113,2
Energy class	A+

