

# DECLARATION OF PERFORMANCE ACCORDING TO REGULATION (EU) 305/2011

No. C110-CPR-251015

# Contura

## PRODUCT

Type designation	Contura 110
Type	Wood burning stove
Air tightness class	Type: BE
Fuel	Wood
Intended area of use	Space heating in residential buildings

## MANUFACTURER

Name	Contura AB
Address	Box 134, Skulptörvägen 10 SE-285 23 Markaryd, Sweden

## VERIFICATION

According to AVCP	System 3
European standard	EN 16510-2-1:2022
Test institute	Danish Technological Institute, NB 1235

## DECLARED PERFORMANCE

Permitted load of chimney	120 kg		
<b>MINIMUM DISTANCE TO FLAMMABLE MATERIALS</b>		<b>CHIMNEY SAFETY REQUIREMENTS</b>	
To the rear ( dR )	150 mm	Minimum safety class	T400
To the side ( dS )	400 mm	<b>CHIMNEY CALCULATION DATA AT NOMINAL OUTPUT</b>	
To the ceiling ( dC )	750 mm	Flue gas outlet temperature	349°C
To the side in radiation direction ( dL )	0 mm	Minimum flue draught	12Pa
In front in direction of radiation ( dP )	1200 mm	Flue gas mass flow	4,5 g/s
To the floor ( dB )	220 mm	<b>CHIMNEY CALCULATION DATA AT PART LOAD OUTPUT</b>	
To the floor in front ( dF )	0 mm	Flue gas outlet temperature	NPD
Protective insulating material	-	Minimum flue draught	NPD
<b>NOMINAL HEAT OUTPUT</b>		Flue gas mass flow	NPD
Space heat output	5,0 kW	<b>SPACE HEATING EFFICIENCY</b>	
Water heat output	NPD	Seasonal space heating efficiency at nominal heat output	69%
Efficiency	79%	Energy Efficiency Index (EEI)	105
<b>PART LOAD HEAT OUTPUT</b>		Energy efficiency class	A
Space heat output	NPD	Electric power consumption at nominal heat output	NPD
Water heat output	NPD	Electric power consumption at part load heat output	NPD
Efficiency	NPD	Power consumption in standby	NPD
<b>EMISSIONS AT NOMINAL HEAT OUTPUT AT 13% O<sub>2</sub></b>		<b>SUSTAINABLE USE OF NATURAL RESOURCES</b>	
Carbon monoxide (CO)	1500 mg/m <sup>3</sup>	Environmental sustainability	NPD
Nitrogen oxides (NO <sub>x</sub> )	200 mg/m <sup>3</sup>		
Organic gaseous carbon (OGC)	120 mg/m <sup>3</sup>		
Particulate matter (PM)	40 mg/m <sup>3</sup>		
<b>EMISSIONS AT PART LOAD HEAT OUTPUT AT 13% O<sub>2</sub></b>			
Carbon monoxide (CO)	NPD		
Nitrogen oxides (NO <sub>x</sub> )	NPD		
Organic gaseous carbon (OGC)	NPD		
Particulate matter (PM)	NPD		

This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011, whereby the undersigned is responsible for the manufacture and compliance with the declared performance.



Nicholas Németh, CEO Contura AB  
Markaryd, 15 October 2025

