

Front View: Shows the unit's dimensions: total height 2150 mm, width 572 mm, and base height 1623 mm. The base has a width of 576 mm and a height of 203 mm. The unit is mounted on a "Tulenarka katto" (fireproof ceiling).

Side View: Shows the unit's profile with dimensions: total height 1192 mm, base height 587 mm, and base width 138 mm. The unit is mounted on a "Tuloilmaliitäntä Ø67" (air intake connection Ø67). The side view also shows the "OD 150" (outer diameter 150 mm) and "ID 150" (inner diameter 150 mm) of the duct.

Installation Details:

- ASENNUS TULENARKAA SEINÄÄ VASTEN (Installation against fireproof wall):** Shows the unit mounted on a wall with a fireproof ceiling. The unit is secured with four screws. The distance from the wall to the unit is 50 mm. The unit's height is 616 mm, and its width is 570 mm. The distance from the wall to the unit's base is 333 mm. The unit's base is 50 mm wide. The unit's base is 570 mm wide. The unit's base is 570 mm wide. The unit's base is 570 mm wide.
- ASENNUS PALOMUURIA VASTEN (Installation against fire wall):** Shows the unit mounted on a wall with a fireproof ceiling. The unit is secured with four screws. The distance from the wall to the unit is 50 mm. The unit's height is 616 mm, and its width is 570 mm. The distance from the wall to the unit's base is 333 mm. The unit's base is 50 mm wide. The unit's base is 570 mm wide. The unit's base is 570 mm wide. The unit's base is 570 mm wide.

Legend:

- A = korkeus lattiasta kannen savupiippuliitäntään (Height from floor to roof duct connection)
- B = korkeus lattiasta taakse lähtevän savupiippuliitäntän keskelle (Height from floor to center of rear duct connection)
- C = korkeus lattiasta tuloilmaliitäntään (Height from floor to air intake connection)
- D = korkeus lattiasta luukun alareunaan (Height from floor to bottom of door)
- ID (Sisähalkaisija) (Inner diameter)
- OD (Ulkohalkaisija) (Outer diameter)

* Jos takka asennetaan esim. lasista valmistetulle eduslevylle (lisävaruste), korkeus lattiasta pienenee eduslaatan paksuuden verran. Irrallinen lasinen eduslevy suurentaa liitäntäkorkeutta hormiin 10 mm:llä.

****** Maalattujen seinien väriäytymisen välttämiseksi suosittelemme samoja suojaetäisyyksiä kuin tulenarkaan seinään.